



## Community Development Department Assessory Dwelling Unit (ADU) Supplemental Form

PO Box 777 • 323 N.E. First Street

Winlock, WA 98596-0777  
360.785.3811 • fax 360.785.4378

[winplan@cityofwinlock.com](mailto:winplan@cityofwinlock.com)

*The form must be included with your application.*

### Check all that Apply:

- Attached/Addition
- Detached (new)
- Detached (conversion of existing)
  - Existing use type: \_\_\_\_\_
- Interior conversion of first or upper floor
- Interior conversion of existing basement (un-heated)
- Interior conversion of existing basement (heated)
- Interior conversion of a garage

### Zoning Information

- Lot Size: \_\_\_\_\_ sq. ft.
- Building Lot Coverage (total sq. ft. of existing buildings on lot ÷ lot sq. ft.) \_\_\_\_\_
- Proposed Building Lot Coverage (total sq. ft. of existing buildings + ADU ÷ lot sq. ft.) \_\_\_\_\_
- Size of ADU: \_\_\_\_\_ sq. ft.
- Net Floor Area (square footage of the **living space** of the **primary unit**, excludes garage) \_\_\_\_\_
- Length of the primary unit including the garage, face the street \_\_\_\_\_
- Length of the ADU facing and visible from the street \_\_\_\_\_
- Height of ADU \_\_\_\_\_

*Maximum size of the ADU shall not exceed 800 sq. ft. or 50% of the primary single-family structure, not including garage and/or detached accessory buildings (whichever is less). ADUs created entirely within existing basements may exceed 800 sq. ft. provided they are not larger than the size of the remainder of the overall home.*

### Building Specific Considerations

All types of ADUs require the entrance to the ADU to be a locking door separate from the entry door to the primary dwelling unit. Electrical circuit breakers and temperature controls (water heater, water disconnect, heating source electrical panel, and gas shut off) must be located in the dwelling unit that they service or be located in common areas accessible to all residents. If a new electrical subpanel is installed, load calculations need to be submitted.

The existing electrical service may need to be upgraded at the transformer and overhead lines may need to be relocated for the ADU. Contact Lewis County PUD to request verification of transformer capacity and required clearances of overhead lines.

A detached ADU requires 10-foot separation from the primary residence or fire-rated construction at the nearest exterior wall, including any stairs or other projections located within 10 feet.

An attached ADU requires a tested one-hour fire rated assembly with a sound transmission class of 50 separating the ADU from the primary dwelling. Smoke detectors and carbon monoxide alarms are required in both units.

An ADU created by interior conversion located fully within the existing residence (no addition), may be exempt from fire and sound separation between the primary dwelling and the ADU when interconnected smoke alarms are provided throughout the entire structure.

Conversion of non-heated space to heated (i.e., un-finished basement or garage) must meet energy code requirements, including insulation upgrades and additional efficiency credits. Basement conversions require minimum ceiling heights and code-compliant stairs or separate exterior door access.